

## MB-2 adf

MB-2 adf is the latest model of PR2 plus family, the world's most popular banking teller printer. MB-2 adf is equipped with automatic document feeder, capable to manage multiple documents and cheque processing, all with frontal insertion, frontal or top ejection and sorting when needed. Using integrated scanner, MB-2 adf enables a complete cheque truncation procedure. MB-2 adf manages a wide range of documents, including ID cards, multiple sheets, passbooks and passports. MB-2 adf can read OCR, barcode and MICR, and enable bill payments.

MOST COMPLETE MULTIFUNCTIONAL TELLER SCANNER AND PRINTER

ABLE TO MANAGE ALL KIND OF BANKING MODULES AND PASSBOOKS

HIGH SPEED AUTO ALIGNMENT

INTEGRATED AUTOMATIC DOCUMENT FEEDER

INTEGRATED DOUBLE OUTPUT SORTING TRAYS

CAN BE SHARED BY TWO OPERATORS

HIGHEST PRINTING SPEED, UP TO 560 CPS

(VHSD MODE)

MULTIPLE INTERFACES, INCLUDING LAN WITH

ON-BOARD IMAGE COMPRESSION

**EASY TO USE** 





Multiple interfaces



Frontal adf, excludible, to automatically insert multiple sheets



Upper sorter to collect printed documents

## **TECHNICAL SPECIFICATIONS**

GENERAL CHARACTERISTICS		
Technology	Impact matrix 24 needles	
Resolution	240 x 360 dpi	
Characters per inch	10, 12, 15, 16.6, 17.1 cpi	
Printing speed	VHSD 560 cps	NLQ 185 cps
(10 cpi)	HSD 510 cps	LQ 125 cps
	Draft 370 cps	BIM 2000 dps
Printing width	238,76 mm (94 columns at 10 cpi)	
Line spacing	1/5", 1/6", n/216", n/240"	
Copies	Original + 6 copies	
Interfaces	USB 2.0, USB Hub, RS232C, Parallel IEEE 1284	
	Optional LAN	
Noise	< 54 dBA (ISO 7779 ECMA 132 text)	
Dimensions (WxDxH)	405 x 415 x 240 mm	
Ribbon Cartridge	10 milions characters	

Document Management	<ul> <li>- Paper path: 245 mm wide</li> <li>- Flatbed</li> <li>- Automatic edge recognition&amp;alignment</li> <li>- Automatic thickness adjustment</li> <li>- Excludible Automatic Document Feeder</li> <li>- Paper trays</li> </ul>	
Emulations	IBM Proprinter2 & XL24 / Epson LQ2550	
Power Consumption	Min. 9W, Max 85W (printing)	
Power Supply	230V / 50Hz, 115V / 60Hz	
Certifications and	CE TuV NRTL	
Security marks	FCC class A verified	
	RoHS	
ADF	Frontal access	
Weight	Approx. 15 Kg	

Performance refers to use of the products in optimal conditions. With the right to change technical characteristics. The registered trademarks are the property of their respective owners.

MB-2 adf is distributed by Olivetti S.p.A.

(09/13) - Code: 29041-01